

Loop Protect

IMPORTANT! THIS GUIDE ASSUMES THAT THE AOS-CX OVA HAS BEEN INSTALLED AND WORKS IN GNS3 OR EVE-NG. PLEASE REFER TO GNS3/EVE-NG INITIAL SETUP LABS IF REQUIRED.

<https://www.eve-ng.net/index.php/documentation/howtos/howto-add-aruba-cx-switch/>

TABLE OF CONTENTS

Lab Objective.....	1
Lab Overview.....	1
Lab Network Layout.....	2
Lab Tasks	2
Task 1 – Lab setup	2
Task 2 – Configure VLANs and Interfaces	3
Task 3 – Enable loop protect on Switch1	3
Task 4 – Enable loop and verify loop is prevented on Switch1.....	5
Appendix – Complete Configurations.....	6

Lab Objective

This lab will provide hands on experience with the Loop Protect feature in AOS-CX.

Loop protect is helpful in environments where STP cannot be used to detect and prevent loops in an L2 network.

Lab Overview

This lab as shown in Figure 1 has 3 switches connected in a loop.

In this lab, you will:

- Configure 802.1Q trunks with 2 VLANs between the 3 switches
- Create an L2 loop between the 3 switches
- Use packet capture to identify loop protect packets being sent out of a switch
- Ensure loop protect detects and prevents a loop by shutting down a port

Lab Network Layout




Figure 1. Lab topology and addresses

Lab Tasks

Task 1 – Lab setup

For this lab refer to Figure 1 for topology and IP address details.

- Start all the devices, including hosts
- Open each switch console and log in with user “admin” and hit enter, so that no password is applied
- Set your desired password
- Change all hostnames as shown in the topology:

```
configure
hostname ...
```

- On all devices, bring up required ports:

```
int 1/1/1-1/1/6
no shutdown
use "exit" to go back a level
```

- Validate LLDP neighbors appear as expected on each switch

```
show lldp neighbor
```

Switch1

```
Switch1(config)# sh lld nei
```

```
LLDP Neighbor Information
=====
```

```
Total Neighbor Entries      : 2
Total Neighbor Entries Deleted : 0
Total Neighbor Entries Dropped : 0
Total Neighbor Entries Aged-Out : 0
```

LOCAL-PORT	CHASSIS-ID	POR-T-ID	PORT-DESC	TTL	SYS-NAME
1/1/2	08:00:09:8a:14:fa	1/1/1	1/1/2	120	Switch2
1/1/3	08:00:09:12:8e:9e	1/1/2	1/1/2	120	Switch3

Task 2 – Configure VLANs and Interfaces

- Configure interfaces, 802.1Q trunks and required VLANs on these 3 switches

switch1

```
Switch1(config)# vlan 10-11
Switch1(config-vlan-<10-11>)# int 1/1/2-1/1/3
Switch1(config-if-<1/1/2-1/1/3>)# no routing
Switch1(config-if-<1/1/2-1/1/3>)# vlan trunk allowed 10-11

! We will shut down 1/1/3 for now to break the loop
Switch1(config-if-<1/1/2-1/1/3>)# int 1/1/3
Switch1(config-if)# shu
```

switch2

```
Switch2(config)# vlan 10-11
Switch2(config-vlan-<10-11>)# int 1/1/1-1/1/2
Switch2(config-if-<1/1/1-1/1/2>)# no routing
Switch2(config-if-<1/1/1-1/1/2>)# vlan trunk allowed 10-11
```

switch3

```
Switch3(config)# vlan 10-11
Switch3(config-vlan-<10-11>)# int 1/1/1-1/1/2
Switch3(config-if-<1/1/1-1/1/2>)# no routing
Switch3(config-if-<1/1/1-1/1/2>)# vlan trunk allowed 10-11
```

Task 3 – Enable loop protect on Switch1

- Enable loop protect on ports to other switches, enabling it on 1 VLAN will be sufficient to detect loops

```
Switch1(config)# int 1/1/2-1/1/3
Switch1(config-if-<1/1/2-1/1/3>)# loop-protect 英文版缺少此命令
Switch1(config-if-<1/1/2-1/1/3>)# loop-protect vlan 10
```

- Verify loop protect on ports

```
Switch1(config-if-<1/1/2-1/1/3>)# do sh loop-protect
```


Status and Counters - Loop Protection Information

Transmit Interval	: 5 (sec)
Port Re-enable Timer	: Disabled
Loop Detected Trap	: Disabled

Interface 1/1/2	
Loop-protect enabled	: Yes
Loop-Protect enabled VLANs	: 10
Action on loop detection	: TX disable
Loop detected count	: 0
Loop detected	: No
Interface status	: up

Interface 1/1/3	
Loop-protect enabled	: Yes
Loop-Protect enabled VLANs	: 10
Action on loop detection	: TX disable
Loop detected count	: 0
Loop detected	: No
Interface status	: down

- Start a packet capture on Switch1 (1/1/2) connected to Switch2



- You should see the protocol ID: 0x0003 packets being sent into the network that are used for loop protect detection with source MAC info

Task 4 – Enable loop and verify loop is prevented on Switch1

- On Switch1, unshut 1/1/3 to create loop

Switch1

```
Switch1(config-if-<1/1/2-1/1/3>)# int 1/1/3
Switch1(config-if)# no shu
```

If a loop protect packet is received by the same switch that sent it, it indicates a loop exists and one of the following actions is taken:

- Discovery of the loop is logged but port states are not changed
 - The sending port is disabled
 - The sending and receiving ports are both disabled
-
- Verify loop is detected and prevented as 1 of the ports is disabled (default loop protect behaviour)

```
Switch1(config-if)# do sh loop-pro
```

Status and Counters - Loop Protection Information

```
Transmit Interval      : 5 (sec)
Port Re-enable Timer  : Disabled
Loop Detected Trap    : Disabled
```

Interface 1/1/2
 Loop-protect enabled : Yes
 Loop-Protect enabled VLANs : 10
 Action on loop detection : TX disable
 Loop detected count : 1
 Loop detected : Yes
 Detected on VLAN : 10
 Detected at : 2021-06-09T22:57:12
 Interface status : down

Interface 1/1/3
 Loop-protect enabled : Yes
 Loop-Protect enabled VLANs : 10
 Action on loop detection : TX disable
 Loop detected count : 0
 Loop detected : No
 Interface status : up

Appendix – Complete Configurations

- If you face issues during your lab, you can verify your configs with the configs listed in this section
- If configs are the same, try powering off/powering on the switches to reboot them

Switch1

```
Switch1# sh run
Current configuration:
!
!Version ArubaOS-CX Virtual.10.07.0004
!export-password: default
hostname Switch1
user admin group administrators password ciphertext
AQBapfLDQUyYkc7G8jiILYsVnVobj/u9GrYoWrQhC8Bh+ntZYgAAAKOg2fGgyuPFaVC3uFWTFi6WvU6/1BdR2bZw0wU/WN0
Cj7UO55iWY2vKztqXIDrAQdc8TAuZkFGwg0Jp3by5k2
uqtI6kkkQvRzTUxHB0orUP0ke1I/qbUjfR3Mh+nJpQ9023
led locator on
ntp server pool.ntp.org minpoll 4 maxpoll 4 iburst
ntp enable
!
!
!
!
!
!
ssh server vrf mgmt
vlan 1,10-11
interface mgmt
    no shutdown
    ip dhcp
interface 1/1/1
    no shutdown
interface 1/1/2
    no shutdown
    no routing
    vlan trunk native 1
    vlan trunk allowed 10-11
    loop-protect
    loop-protect vlan 10
interface 1/1/3
    no shutdown
    no routing
    vlan trunk native 1
    vlan trunk allowed 10-11
    loop-protect
    loop-protect vlan 10
interface 1/1/4
    no shutdown
interface 1/1/5
    no shutdown
interface 1/1/6
    no shutdown
!
!
!
!
https-server vrf mgmt
https-server vrf mgmt
```

switch2

```
Switch2# sh run
Current configuration:
!
!Version ArubaOS-CX Virtual.10.07.0004
!export-password: default
hostname Switch2
user admin group administrators password ciphertext
AQBapThMptxqFInprZFYSpfPwBfxijWFnBfUzZe+BxJ5fLofYgAACZtxwdeBkcZfgVmJccElku3trTvX1kGFIaiejEGkNK
Ok8biKq/n9Es5h1jhrzPDjYgz6caIUuPIoZDok8GL2u
3aegtAv9K3DtF2299xDkEhzwUJneH94hoWxsLEjkGU9ffFa
led locator on
ntp server pool.ntp.org minpoll 4 maxpoll 4 iburst
ntp enable
!
!
!
!
!
!
!
ssh server vrf mgmt
vlan 1,10-11
interface mgmt
    no shutdown
    ip dhcp
interface 1/1/1
    no shutdown
    no routing
    vlan trunk native 1
    vlan trunk allowed 10-11
interface 1/1/2
    no shutdown
    no routing
    vlan trunk native 1
    vlan trunk allowed 10-11
interface 1/1/3
    no shutdown
interface 1/1/4
    no shutdown
interface 1/1/5
    no shutdown
interface 1/1/6
    no shutdown
!
!
!
!
https-server vrf mgmt
```

switch3

```
Switch3# sh run
Current configuration:
!
!Version ArubaOS-CX Virtual.10.07.0004
!export-password: default
hostname Switch3
user admin group administrators password ciphertext
AQBapVspfXYst0T2YjNexlVhZr+WzEpljJGdqToDdwVsSNp7YgAAAE82gWYabqopE61bU2c/Z5C5cOJgoIqRc/LbA2S2gVu
7pulAJqtp7NOhYtmOdwKUXmv4ybky gabKIKEUs5IRDm
G/H1JnB2Poo44H+MI/m8J8dmI0Yn9xuDzyGu/TCozjgn+a
led locator on
```

```
ntp server pool.ntp.org minpoll 4 maxpoll 4 iburst
ntp enable
!
!
!
!
!
!
ssh server vrf mgmt
vlan 1,10-11
interface mgmt
    no shutdown
    ip dhcp
interface 1/1/1
    no shutdown
    no routing
    vlan trunk native 1
    vlan trunk allowed 10-11
interface 1/1/2
    no shutdown
    no routing
    vlan trunk native 1
    vlan trunk allowed 10-11
interface 1/1/3
    no shutdown
interface 1/1/4
    no shutdown
interface 1/1/5
    no shutdown
interface 1/1/6
    no shutdown
!
!
!
!
!
https-server vrf mgmt
```



www.arubanetworks.com

3333 Scott Blvd. Santa Clara, CA 95054
1.844.472.2782 | T: 1.408.227.4500 | FAX: 1.408.227.4550 | info@arubanetworks.com